

LISTING OF THE CLAIMS

The following listing of claims replaces all prior claim listings and versions:

1. (Currently Amended) An arrangement for recirculation of exhaust gases in a supercharged combustion engine, the arrangement comprising:

an exhaust line operable configured to lead the exhaust gases out from the combustion engine;

an inlet line operable configured to lead air at above atmospheric pressure to the combustion engine; and

a return line comprising:

a connection to the exhaust line and a connection to the inlet line positioned and configured so that the return line is operable configured to recirculate the exhaust gases from the exhaust line to the inlet line; [[and]]

a second cooler operable provided to cool the exhaust gases in the return line by use of a liquid medium in the second cooler;

a first cooler using ambient air as a cooling medium and operable configured to cool the exhaust gases and incorporated in the return line downstream from the second cooler and upstream from a mixture point where the exhaust gases are mixed with the air in the inlet line; and

a third cooler configured to cool the air in the inlet line before the air is mixed with the exhaust gases from the return line,

wherein the first cooler is positioned in close physical proximity to the third cooler such that the first cooler and the third cooler together comprise a flat integrated cooler package having a main extent in one plane, the first cooler positioned relative to the third cooler such that both have the main extent in the one plane.

2. (Currently Amended) The arrangement according to claim 1, further comprising a cooling system in which the liquid medium is circulated and the cooling system is operable configured to cool the combustion engine using the liquid medium.

Claims 3. - 6. (Canceled)

7. (Currently Amended) The arrangement according to claim 8, further comprising a fourth cooler positioned in close physical proximity to the first cooler and the to third cooler, the fourth cooler being ~~operable~~ configured to cool the coolant in a cooling system.

8. (Currently Amended) The arrangement according to claim 2, further comprising a third cooler ~~operable~~ configured for cooling the air in the inlet line before the air is mixed with the exhaust gases from the return line.

9. (Currently Amended) The arrangement according to claim [[3]]1, wherein the first cooler and the third cooler are each formed as a flat cooler package having a main extent in one plane, the first cooler positioned relative to the third cooler such that both have the main extent in the one plane.

10. (Currently Amended) The arrangement according to claim [[5]]1, further comprising:

a cooling system in which the liquid medium is circulated and the cooling system is ~~operable~~ configured to cool the combustion engine; and

a fourth cooler disposed in close physical proximity to the first cooler and to the third cooler, the fourth cooler ~~operative~~ configured to cool the coolant in the cooling system.